

Gobo Size

Gobo Size reference table, please refer to manufacturers' user manual for more

Conventional Size	Model	Outer Diameter	Image Diameter
	A Size	100 mm	58 mm
	B Size	86 mm	60 mm
	D Size	53.3 mm	43 mm
	E Size	37.5 mm	28 mm
	G Size	51.8 mm	43 mm
	M Size	66 mm	43 mm
	V Size	22.5 mm	22 mm
Altman	Model	Outer Diameter	Image Diameter
	3.5Q	53 mm	43 mm
	360/360Q	82 mm	58 mm
	Master Ellipse	37.5 mm	29 mm
	Micro Ellipse	37.5 mm	29 mm
American DJ	Model	Outer Diameter	Image Diameter
	Accu Color 250	26.2 mm	25.5 mm
	Accu Scan 250	25 mm	20 mm
	Accu Spot 250	24 mm	20 mm
	Accu Spot 250 Hybrid	26.7 mm	24 mm
	Accu Spot 250 II	25 mm	20 mm
	Accu Spot 250 PRO	26.7 mm	24.7 mm
	Accu Spot 300	25 mm	20 mm
	Auto Spot 150	27.8 mm	18 mm
	Gobo Projector LED	26.8 mm	24 mm
	Icon	26 mm	20 mm
	Image 250	53.3 mm	28 mm
	IKON LED	54mm	33mm
	IKON profile	26.8mm	24mm
	PinPoint Gobo	25.8mm	19mm
	Roto Gobo	26 mm	22 mm
	Vizi Spot Pro	26.6 mm	23.8 mm
	Whirl	26 mm	20 mm
	X-Color LED	22.5 mm	17 mm
Chauvet	Model	Outer Diameter	Image Diameter
	DMX 690	23.7 mm	17.5 mm
	EZGobo LED	25.8mm	18.6mm (metal only)
	Followspot 400G TFX-FS360	35.8 mm	27.8 mm
	Gobo Zoom LED	28.8 mm	24.3 mm
	Gobo Zoom LED 2.0	28.6 mm	26 mm
	Gobo Zoom USB	25.74mm	19.38mm
	ILS 515DMR	26.8 mm	21 mm
	ILS 515M	27 mm	19 mm
	ILS 606DBR	27 mm	19 mm
	ILS 606DSR	27 mm	19 mm

ILS 625DCR	27 mm	19 mm
Intimidator Barrel LED 300	23.8 mm	20.9 mm
Intimidator Scan LED 300	23.8 mm	20.9 mm
Intimidator Spot 2.0 HTI	23.5 mm	17.5 mm
Intimidator Spot 250	26.7 mm	24.5 mm
Intimidator Spot LED 250	24 mm	20 mm
Intimidator Spot LED 350/355	24 mm	20 mm
Intimidator Spot XYZ	23.8 mm	20 mm
Legend 1200E Spot	37.3 mm	30 mm
Legend 150 R	26.5 mm	21 mm
Legend 2000	31 mm	20 mm
Legend 250 RX	26.5 mm	19 mm
Legend 3000	31 mm	24 mm
Legend 3000X	29 mm	24 mm
Legend 300E Spot	26.8 mm	23.9 mm
Legend 5000	29 mm	24 mm
Legend 5000X	29 mm	24 mm
Legend 550	26.7 mm	22 mm
LFS-5(d)	25.4 mm	19 mm
LFS-75 DMX	40 mm	18 mm
Q-Scan 150	27.7 mm	21.5 mm
Q-Scan 250	27.7 mm	21.5 mm
Q-Spot	27 mm	19 mm
Q-Spot 150	27 mm	19 mm
Q-Spot 150 LED	25.7 mm	18 mm
Q-Spot 152	25 mm	21 mm
Q-Spot 160 LED	25.8 mm	18.2 mm
Q-Spot 200	25.6 mm	20.5 mm
Q-Spot 250	37.2 mm	30 mm
Q-Spot 260 LED	25.95 mm	19 mm
Q-Spot 300	37 mm	28 mm
Q-Spot 560 LED	32.5 mm	27 mm
Q-Spot 575	31 mm	22.5 mm
SX - Gobo	53.3 mm	45 mm
Trackscan 250 R	26.8 mm	18 mm

Clay Paky	Model	Outer Diameter	Image Diameter
	Alpha Profile 1200	37.5 mm	25 mm
	Alpha Spot 575	37.5 mm	25 mm
	Alpha Spot 700	37.5 mm	25 mm
	Alpha Spot Easy 1200	37.5 mm	25 mm
	Alpha Spot HPE 1200	37.5 mm	25 mm
	Alpha Spot HPE 300	25.7 mm	23 mm
	Alpha Spot HPE 575	37.5 mm	25 mm
	Golden Scan	66 mm	43 mm
	Golden Scan HPE	51.8 mm	36 mm
	Golden Spot 1200	51.8 mm	36 mm
	MiniScan HP3	25.8 mm	19 mm

S.I.P. 300	31.5 mm	24 mm
Stage Profile Plus	51.8 mm	48.7 mm
Stage Scan	51.8 mm	36 mm
Stage Zoom 1200	51.8 mm	36 mm
Super Scan	66 mm	57 mm
Super Scan Zoom	51.8 mm	36 mm
Tiger Scan	51.8 mm	36 mm
V.I.P. 1200	31.5 mm	24 mm
V.I.P. 150	31.5 mm	24 mm
V.I.P. 250 ALO	31.5 mm	24 mm
V.I.P. 250 ALO/ST	31.5 mm	24 mm
V.I.P. 300	51.8 mm	33 mm
V.I.P. 300 DIA	51.8 mm	33 mm

Coemar	Model	Outer Diameter	Image Diameter
---------------	--------------	-----------------------	-----------------------

CF 7 HE	25.8 mm	19.5 mm
I Profile Flex	32.8 mm	28 mm
I Spot 1200	32.8 mm	28 mm
I Spot 150	32.9 mm	29 mm
I Spot 575	32.9 mm	26 mm
I Spot Flex	32.8 mm	28 mm
Infinity Spot S	27 mm	21 mm
Infinity Spot XL	32.8 mm	25 mm
NAT MM 1200 Zoom BBI	50 mm	37.5 mm
NAT MM 2500 Zoom	50 mm	37.5 mm
NAT MM 4000 Zoom	50 mm	37.5 mm
ProSpot 150	32.9 mm	26 mm
ProSpot 250 LX	25.8 mm	19 mm
ProSpot 575	32.9 mm	26 mm
Unknown	26.8 mm	21 mm

Elation	Model	Outer Diameter	Image Diameter
----------------	--------------	-----------------------	-----------------------

Active Scan 250	26.9 mm	23 mm
Active Wave 250	26.9 mm	23 mm
Color Spot 575	27 mm	23 mm
Design Spot 1400	37.5 mm	31 mm
Design Spot 250	27 mm	20 mm
Design Spot 250WH	27 mm	23 mm
Design Spot 300 Pro	26.9 mm	23 mm
Design Spot 575	26.9 mm	23 mm
Design Spot LED	26.9 mm	24 mm
E Spot LED	26.9 mm	24 mm
ELAR Image X	37.5 mm	20 mm
ELAR Image XR	37.5 mm	20 mm
Focus Spot 250	27 mm	24 mm
Image IP2	51.8 mm	35.5 mm
Image Pro 300	51.8 mm	35.5 mm
Image Pro 300 Rotating Wheel (IP-RGW)	31.5 mm	23 mm

Joy-150	26 mm	22 mm
Joy-300	26 mm	22 mm
Patend 1200	37.5 mm	27 mm
Platinum Spot 5R	14 mm	7 mm
Power Spot 250	27 mm	23 mm
Power Spot 575	26.9 mm	23 mm
Power Spot 575IE	26.9 mm	23 mm
Power Spot 700	26.9 mm	23 mm
Power Spot 700 CMY II	26.9 mm	23 mm
Vision Scan 250	27 mm	23 mm
Vision Scan 575	22.5 mm	18 mm

ETC	Model	Outer Diameter	Image Diameter
	Revolution	66 mm	59 mm
	Source Four	86 mm	59 mm
	Source Four Jr	66 mm	43 mm

High End Systems	Model	Outer Diameter	Image Diameter
	Cyberlight	44 mm	36 mm
	Cyberlight Turbo	44 mm	38 mm
	Image Marketing Projector	37.5 mm	35 mm
	Intellabeam	25 mm	22 mm
	Intellabeam 700 HX	25 mm	22 mm
	SHOWGUN	64.9 mm	53 mm
	Studio Spot 250	25 mm	19 mm
	Studio Spot 575	36.4 mm	31.75 mm
	Technobeam	25 mm	20 mm
	Technobeam FX Wheel	36 mm	26 mm
	Trackspot	25 mm	22 mm
	X-Spot	36.4 mm	31.75 mm

Martin Professional	Model	Outer Diameter	Image Diameter
	CX-10	22.5 mm	17 mm
	EGO 1-3	22.5 mm	16 mm
	Exterior 1200 Image Projector	53.3 mm	48 mm
	Imagescan	53.3 mm	44 mm
	Mac 2000 Rotating	37.5 mm	30 mm
	Mac 250 / 250+	22.5 mm	17 mm
	Mac 250 Entour	22.5 mm	17 mm
	Mac 250 krypton	22.5 mm	17 mm
	Mac 350 Entour	27.9 mm	23 mm
	Mac 500	27.9 mm	23 mm
	Mac 550 Profile	27.9 mm	23 mm
	Mac 575 Krypton	27.9 mm	23 mm
	Mac 700 Profile	27.9 mm	23 mm
	Mac III Profile	37.5 mm	30 mm
	Mania DC3	54 mm	38 mm
	Mania EF3	54 mm	43 mm
	Mania PR1	53.3 mm	40 mm
	Mania SCX-600	22.5 mm	17 mm

Mania SCX-700	22.5 mm	17 mm
Mania SCX-800	22.5 mm	17 mm
Mini Mac Maestro	37.5 mm	30 mm
Mini Mac Profile	22.5 mm	17 mm
MX-10	22.5 mm	17 mm
RoboScan Pro 518	21.5 mm	14 mm
RoboScan Pro 918	27.9 mm	23 mm
SmartMAC	27.9 mm	23 mm

Robe	Model	Outer Diameter	Image Diameter
	ClubSpot 250	26.8 mm	19 mm
	ColorSpot 1200	37.5 mm	29 mm
	ColorSpot 170	26.8 mm	19 mm
	ColorSpot 250	26.8 mm	19 mm
	ColorSpot 575	26.8 mm	19 mm
	ColorSpot 700E AT	26.8 mm	22 mm
	Image Spot 250	37.5 mm	29 mm
	MS Zoom 250	37.5 mm	19 mm
	Scan 250	26.8 mm	19 mm
	Scan 575	26.8 mm	19 mm
	Spot 160	26.8 mm	19 mm
	Spot 250	26.8 mm	19 mm
	Spot 575	26.8 mm	19 mm